

I BENEFIT


























tilebarlyt


Optoro | Scarlet Oak Coppertone | 6"x48" | Floor











































SLATE



tilebarlyt

Optoro | Trail Slate Dark Gray | 12"x24" | Floor









MARBLE

tilebar

Optoro | Chauny Marble Dark Beige | 12"x24" | Floor












tilebar

Optoro | Juneau Sandstone Light Gray | 12"x24" | Floor







SIZES + FORMATS 12"x24"

6"x48"

DESIGN	SIZE	28 MIL	12 MIL
Spice Birch Moon	6x48	•	
Scarlet Oak Fawn	6x48	•	
Amur Maple Monticello	6x48	•	•
Tekapo Oak Scotch	6x48	•	•
Scarlet Oak Coppertone	6x48	•	•
Driftwood Rialto	6x48	•	=
Oregon Maple Tualatin	6x48	•	•
Spice Birch Dockside	6x48	•	•
Spice Birch Meadow	6x48	•	=
Tekapo Oak Loft	6x48	•	=
Brazilian Walnut Cocoa	6x48	•	=
Bur Oak Brindle	6x48	•	
Limed Oak Harbor	6x48	•	=
Scarlet Oak Studio	6x48	•	•
Bur Oak Veranda	6x48	•	=
Spice Birch Toast	6x48	•	
Trail Slate Black	12×24	•	=
Trail Slate Dark Gray	12×24	•	-
Trail Slate Light Gray	12×24	•	=
Trail Slate Beige	12×24	•	-
Juneau Sandstone Dark Beige	12×24	•	=
Juneau Sandstone Dark Gray	12×24	•	-
Juneau Sandstone Medium Gray	12×24	•	=
Juneau Sandstone Light Gray	12×24	•	
Chauny Marble Beige	12×24	•	
Chauny Marble Dark Beige	12×24	•	
Chauny Marble Dark Gray	12×24	•	
Chauny Marble Medium Gray	12×24	•	=

In Stock | ■ Available to Order

Select colors from 12 mil wear layer thickness available by Special Order Only. Minimum order one pallet, with an 8-12 week lead time.

LUXURY THAT CLICKS

Quiet, luxury comfort with exceptional under-foot feel. Optoro is the combined product of the industry's best flooring features and thousands of research hours to bridge the gap between luxe natural flooring and modern-day maintenance. Experience 28 natural stone and wood looks that can endure lifetimes of heavy-duty traffic.

EASY INSTALL

Built-in UNILIN
angle/drop locking
system clicks panels
into place for a
sure-fit floor that
you can walk on in
an instant. No messy
grouts or sticky glues.
Just snap in place,
it's ready to use!

EVERYTHING PROOF

The solid polymer core makes Optoro great for any room in any season without stains, swelling or expansion even in high temperatures.

EASY MAINTENANCE


Beautiful hardwood or stone looks that offer unmatched durability and performance. Easily clean spills with Optoro's waterproof construction and level seamless joints, simply sweep and mop. No sanding, varnishing, staining, or sealing required.

NOISE DAMPENING

Optoro flooring creates exceptional soundproofing, our acoustic backing softens footsteps so you can hear a little less of the upstairs neighbors.

BREATHE EASIER

Flooring made from sustainably produced materials that are low VOC for better indoor air quality. Optoro floors are recyclable at any point in the flooring lifecycle to be better for our world.



PROTX™ Topcoat

Our trademarked, UV-cured urethane topcoat protects against abrasions and provides industry-leading scratch, scuff, stain, and chemical resistance for an easy-clean, beautiful floor.

- Wear Layer | 40% Stronger than the industry standard A textured layer of micro-beveled PVC that protects against rips, tears, and indentations to extend the life and durability of the floor.
- High-Resolution Decorative Print Film Proprietary print technology gives Tilebar Luxury Vinyl Tile an exceptionally realistic style and uncompromising visual quality.
- Waterproof Solid Polymer Core

A solid, single-material core creates both dimensional and dynamic stability to withstand heavy foot traffic and rolling loads under 500lbs. Our built-in UNILIN angle/drop locking system makes for easy installation while castor-tested ledging ensures level, seamless joints and smooth rolling.

Acoustic IXPE Backing

An extra layer of softening and soundproofing to ensure long-term comfort and exceptional acoustic dampening.

ITECHNICAL DATA

28 MIL SPECIFICATIONS			
In Stock and Ready to Ship			
Available Sizes:	12" x 24" 6" x 48"		
Construction:	Rigid Core Luxury Vinyl Tile		
Classification:	ASTM F3261 Class I, Type B, Grade I, Backing Class B		
Total Thickness:	5.0mm (0.200") (Includes 1.0mm Acoustic Backing)		
Wear Layer Thickness:	28mil (0.70mm)		
Edge Treatment:	Micro-Bevel		
Finish:	ProTx™		
Color:	28		
Installation Method:	Rigid Core - Click		
Locking System:	UNILIN Angle/Drop		
Backing Color:	Black		
Pieces per Carton:	14 pcs (12x24) 14 pcs (6x48)		
Weight per Carton:	45.76 lbs (12x24) 45.1 lbs (6x48)		
Square Feet per Carton:	28.04 ft (12x24) 27.39 ft (6x48)		
Cartons per Pallet:	54		

12 MIL SPECIFICATIONS			
Select Colors In Stock			
Available Sizes:	12" x 24" 6" x 48"		
Construction:	Rigid Core Luxury Vinyl Tile		
Classification:	ASTM F3261 Class I, Type B, Grade I, Backing Class B		
Total Thickness:	4.5mm (0.180") (Includes 1.0mm Acoustic Backing)		
Wear Layer Thickness:	12 mil (0.30")		
Edge Treatment:	Micro-Bevel		
Finish:	ProTx™		
Color:	28		
Installation Method:	Rigid Core - Click		
Locking System:	UNILIN Angle/Drop		
Backing Color:	Black		
Pieces per Carton:	14 pcs (12x24) 14 pcs (6x48)		
Weight per Carton:	40.7 lbs (12x24) 39.6 lbs (6x48)		
Square Feet per Carton:	28.04 ft (12x24) 27.39 ft (6x48)		
Cartons per Pallet:	60 (12x24) 66 (6x48)		

Select colors from 12 mil wear layer thickness available by Special Order Only. Minimum order one pallet, with an 8-12 week lead time.

APPLICATIONS

Commercial Spaces: Foot Traffic Only and Light Rolling Loads under 500 lbs., Educational Institutions, Healthcare, Senior Living, Hospitality, Retail, Workplace

Residential: Multi-Family, Single Family

ITESTING SPECIFICATIONS

28 MIL + 12 MIL		
Dimensional Stability (ASTM F2199):	Passes - Max 0.020 in/lin ft	
Squareness (ASTM F540):	Passes - Max ± 0.010	
Flatness (ISO 24337)	Passes	
Opening (ISO 24337)	Passes	
Ledging (ISO 24337)	Passes	
Residual Indentation (ASTM F1914):	Avg. ≤ 0.007 in. (0.18 mm) No puncture thru wear layer/décor to Rigid Core	
Static Load (ASTM F970 mod.):	Passes – Modified Test (anything beyond 250 PSI) = 1,500 PSI; Residual Indent ≤ 0.005"	
Acoustics (ASTM E492)	54 - Over 6" Concrete Slab 68 - Over 6" Concrete Slab and Drop Ceiling	
Flooring Radiant Panel (ASTM E648):	Passes - Class 1; ≥ 0.45 watts/cm2	
Smoke Density (ASTM E662):	Passes - ≤ 450	
Slip Resistance (ASTM D2047):	Passes - SCOF≥ 0.6	
Resistance to Light (ASTM F1515):	Passes - ΔΣ≤ 8.0	
Chemical Resistance (ASTM F925):	Excellent	
Resistance to Heat (ASTM F1514):	Passes	
Castor Chair (EN 425)	Passes	
























Luxurious benefits include micro-beveled panels, sound-dampening acoustic backing, UNILIN angle-drop installation, fiberglass layers and high wear layer options. Explore luxury collections with exquisite value per square foot and a 10-year warranty on every floor.

FORMULATED FOR SUCCESS

Mapping out a winning TileBar LVT solution means choosing the right product for the right application. Heavy Commercial locations with high-weight deliveries? Light Commercial needs for light rolling loads and heavy foot traffic? Multi-Family/Residential needs that can hold up to any wear and tear? With glue-down and click-in installation options available in all categories, TileBar has developed the perfect LVT solution for your application needs.