

BOND RIGID CORE CLICK | VERSALAY | GLUE DOWN

tilebar



POWERED BY PERFORMANCE

Like all TileBar luxury vinyl flooring, Bond LVT is engineered layer-by-layer for optimal performance. It contains a dense core, a thicker-than-most wear layer, and a hardworking topcoat. It resists water, stains, scratches, and indentations. Bond gets its authentic concrete look—complete with nuanced shading—from a high-definition print in the design layer of the product, which is available in five colorways. This collection of 12-by-24-inch, slab-format luxury vinyl tile can be installed using two different methods, so you can choose the one that meets your needs.

WHY BOND LVT?

- A waterproof core provides dimensional stability.
- A tough wear layer resists scratches and indentations.
- High-definition print provides an authentic concrete look.
- Acoustic IXPE foam backing absorbs sound and increases comfort underfoot. (Rigid Core Click and VersaLay Only)
- Suitable for both residential and commercial applications.

CONCRETE LOOKS



PALLADIUM



EXCALIBUR



VIRIDUM



INDIO



VENOM



PET FRIENDLY



ANGLE / CLICK



WATER PROOF



ACOUSTIC VALUE



CASTOR CHAIR APPROVED



BOND RIGID CORE CLICK | VERSALAY | GLUE DOWN



TESTING SPECIFICATIONS	12 MIL 20 MIL 28 MIL
Dimensional Stability (ASTM F2199):	Passes - Max 0.020 in./lin ft
Squareness (ASTM F540):	Passes - Max ± 0.010
Flatness (ISO 24337)	Passes
Opening (ISO 24337)	Passes
Ledging (ISO 24337)	Passes
Residual Indentation (ASTM F1914)	Avg. ≤ 0.007 in (0.16mm) No puncture through wear layer / print film
Static Load (ASTM F970 / Modified))	Passes - Modified Test (anything beyond 250 PSI) - 1,500 PSI: Residual Indent ≤ 0.005"
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM D2047)	Passes - SCOF ≥ 0.6
Resistance to Light (ASTM F1515)	Passes - ΔΣ ≤ 8.0
Chemical Resistance (ASTM F925)	Excellent
Resistance to Heat (ASTM F1514)	Passes
Castor Chair (EN 425)	Passes



TECHNICAL DATA	12 MIL	20 MIL	28 MIL
Available Sizes	12" x 24"	12" x 24"	12" x 24"
Construction	Glue Down	Rigid Core Click	Versalay
Classification	ASTM F1700 Class III, Type B	ASTM F3261 Class I, Backing Class B	ASTM F1700 Class III, Type B
Total Thickness	2.0 mm (0.080")	5.0 mm (0.200") (Includes 1.0 mm Acoustic Backing)	4.5 mm (0.180")
Wear Layer Thickness	12 mil (0.30 mm)	20 mil (0.50 mm)	28 mil (0.70 mm)
Edge Treatment	Square	Micro-Bevel	Micro-Bevel
Finish	ProTX Topcoat™	ProTX Topcoat™	ProTX Topcoat™
Colors	5	5	5
Installation Method:	Full Spread Adhesive	Click	Versalay or Perimeter / Grid / Full Spread Adhesive
Locking System:		Angle/Angle	
Backing Color	Black	Black	Black
Pieces per Carton	20 pcs	10 pcs	9 pcs
Weight per Carton	33 lbs	33 lbs	33 lbs
Square Feet per Carton	40 sf	20 sf	18 sf
Cartons Per Palette	68	68	68

COLORWAYS	SIZE	RIGID CORE CLICK	VERSALAY	GLUE DOWN
Indio	12X24	●	■	●
Excalibur	12X24	●	■	●
Palladium	12X24	●	■	●
Venom	12X24	●	■	●
Viridum	12X24	●	■	●
● In Stock ■ Available to Order				